

Candy

Available colours

Special colour additives

Candy additives are high-quality products designed for use with solvent-based basecoats, allowing the creation of unique and original colours. They enable reproduction of hard-to-match shades such as Mazda 46V and Renault NNP, while also offering flexibility in developing custom colours.

Candy additives are also ideal for creating striking visual effects, making them popular among painters and airbrush artists. Supplied in 0,22-Litre esthetic, metallic bottles, they are suitable for both small and large painting projects. Their high-quality formulation makes them an excellent choice for professionals and enthusiasts seeking distinctive colour results.

PACKAGING	
Volume	Collective packaging
0.22 l	6 pcs.

SOLVENT ADDITIVE

PAINT EFFICIENCY

SATURATED AND VIVID COLOURS

INDIVIDUAL COLOURS

CONVENIENT PACKAGING

RECOMMENDED SIZES FOR PAINT STRAINER

125-190 µm

PAINT EFFICIENCY

according to the colour

COLOURS AVAILABLE:

- C20 yellow
- C30 orange
- C40 red
- C50 blue
- C70 black

MODEL APPLICATION

step I
silver acrylic primer coating (**M9-0306.0**)
step II
coating with a mixture of base resin **B01** and **Candy** (e.g. 90% **B01** + 10% **Candy C50**)
step III
coat application

MINIMUM SHELF LIFE

36 months in originally sealed packaging

VOC

LZO
VOC

2004/42/WE IIB (840) 820

PROCESS

PROGRESS

SUBSTRATE PREPARATION

After preparing and abrading the primer surface, degrease with silicone remover **CP 015** and clean with **CP 011**, then apply the basecoat

MIXING RATIO

Candy is added only to solvent based mixing systems.
For OEM codes, the amount of additive is determined by the recipe found in the formulation software. In case of custom colours, a maximum of **30%** of **Candy** is added

SPRAY GUN SETTINGS

Nozzle size: **1.2-1.4 mm**;
Operating pressure: HVLP/RP **1.8-2.0 bar**

APPLICATION

Application is subject to the specific method and colour that the additive is used with

EVAPORATION TIME AFTER APPLICATION

5-10 min after coating at **20°C** and **65%** relative humidity